

The `crop` package

Melchior FRANZ

Nov 19, 2017

Abstract

This article describes the `crop` package¹, which provides different forms of crop marks for trimming paper stacks, for camera alignment and for visualizing the page dimensions. There are options for centering the document page on the paper sheet, for mounting pages on a physical sheet, for reflecting and inverting the whole document or printing it upside-down, and for suppressing either text or graphics output.

The package was originally developed for needs of the Austrian Red Cross/Federal Province of Vienna/Department of Radiation Protection.

Contents

1	Introduction	2	3.2 Dependencies	9
2	How to use the package	2	4 The implementation	9
2.1	Conventional options	2	4.1 Preamble	9
2.2	Runtime options	3	4.2 The device drivers	10
2.3	Loading	5	4.3 Size options	13
2.4	Color support	6	4.4 Runtime options handling	14
2.5	Custom document page size	6	4.5 Axes and page info	15
2.6	Custom printing paper sheet size	7	4.6 The marks	16
2.7	Defining your own marks	7	4.7 The kernel	18
2.8	The configuration file	8	4.8 Mounting	20
3	How the package works	8	4.9 Page manipulation	21
3.1	The kernel mechanism	8	4.10 Color handling	23
			4.11 The graphics commands	24
			4.12 Final settings	25
			4.13 A <code>mount4</code> example	25

¹This file has version number 1.10, last revised 2017/11/19.
I'd like to thank ROLF NIEPRASCHK for his useful hints and suggestions, which influenced the package substantially. A big thank you also goes to WALTER SCHMIDT for his extensive tests and his expertise on compatibility issues with different devices.

1 Introduction

It is convenient to print documents for smaller logical paper sizes on paper of the printer's standard physical paper size. On the one hand this keeps from changing paper stacks, on the other hand it allows printing close to the logical paper edge and even outside the logical page.

For trimming a whole paper stack or lining up the single pages on printing plates for photographic duplication a set of corner marks is required.

2 How to use the package

2.1 Conventional options

These options may only be used in the preamble and have to be stated as arguments to the `\usepackage` command (as in `\usepackage[mirror]{crop}`).

a0, a1, a2, a3, a4, a5, a6, b0, b1, b2, b3, b4, b5, b6, letter, legal, executive

These options declare the printing paper dimensions. One of them should be specified if the `center` option or one of the options `dvips`, `pdftex`, `lualatex` and `vtx` is used. The size options do not define the logical document page size! See section 2.5 for how to achieve this.

width, height — Instead of using one of the pre-defined paper formats as described above, you can also set the physical paper dimensions directly. You may omit the ‘`true`’ specifier if you don't plan to scale the document. Example: `\usepackage[cam,width=10truecm,height=13truecm]{crop}`

center This option centers the logical document page on the physical printer paper and therefore requires that you declare the sheet size properly. Write, for example, `\usepackage[cam,a4,center]{crop}` to center a document of any size on ISO-A4 sheets.

landscape — Use this option in addition to the `center` option if you want to center a document on *landscape oriented* paper. It has nothing to do with L^AT_EX's `landscape` document class option.

dvips, pdftex, pdflatex, lualatex, lualatex, vtex, nodriver — If you are working with `dvips`, `pdftex`, `pdflatex`, `lualatex` or `vtex` you may want to pass the dimensions of the paper that you are planning to print on to the respective driver program. Especially viewer programs like `evince` or `xpdf` make use of this *bounding box* information. Unfortunately, this can't be done in a generic way—there's no standard. These options select driver specific methods to set the paper size and to rotate and reflect a page.

The `crop` package tries to find out by itself which driver to use. You find its choice mentioned in the log file. Additionally, you can *suggest* (`[dvips]`) or *enforce* (`[dvips!]`) one of the drivers. In the latter case you only have to add an exclamation point to the driver option. The difference is, that

a suggestion may get overruled by the package. Assume you have asked for [dvips], but run the document file through `pdflatex`. In this case `crop` will automatically use the `pdflatex` driver. You can also force `crop` not to use any of the drivers by requesting the `nodriver` option. `pdflatex` is a synonym for `pdftex`, and `lualatex` is a synonym for `luatex`.

- mirror** This option reflects the whole document, provided that the selected output driver supports the `graphics` package's `\reflectbox` command. It doesn't have any effect on the DVI file.
- rotate** Rotates the document by 180° so that it appears upside-down. This may be useful to circumvent problems with printers, which do not print close enough to the lower paper edge due to their paper feed mechanism.
- invert** Lets the whole document be printed white onto black background, if the `color` package can be loaded and the document is output with a color aware device. All further color changing commands stated in the document are disabled. This option doesn't invert pictures, nor does it really swap text and paper color. Red text on green will still become white text on black. `invert` is stronger than `notext`.
- notext** — This option uses the `color` package to turn text to white color, after which all further color switching commands are disabled. This makes the text disappear from the printout, although it remains in the output file. See the description of the options `nographics` and `graphics` on page 5 for an explanation. This option is ignored if option `invert` was also requested.

2.2 Runtime options

These options may be used in the preamble like the ‘conventional’ options (see section 2.1), but also as optional arguments to the `\crop` command everywhere in the document (as in `\crop[frame]`). Using this command without options implies `\crop[cam,noaxes]`.

- cam** This mode provides four different marks (see figure 1), one for each corner. They indicate the logical paper edges without touching them and can thus be printed on every page. These marks are mainly thought for camera alignment. The `\crop` command selects this mode if no other mode is requested.
- cross** This mode provides four 4 cm wide crosses (see figure 1), one at each corner, that touch the logical paper edge. That's why they should be printed on an extra page that will be used as a cover page while trimming the whole paper stack. (This is also the *Red Cross* mode ;-)
- frame** This mode draws a frame around the logical page and is mainly thought for visualizing the document page dimensions.

- off** — This ‘option’ makes only sense in connection with the `\crop` command (i.e. at runtime). It disables all markings and is selected by default if the package is input without requesting any of the marks.
- odd, even** — Use these options to let the crop marks be put on odd/even pages only. They automatically turn on `cam` marks if no other marks have been requested. Note that only the page number is considered. If you have two subsequent pages both with page number 1, and ask for the `odd` option, then both pages will have marks.
- axes, noaxes** — These options enable/disable the output of little marks that indicate the logical page’s horizontal and vertical middle axis and may be selected in addition to one of the main modes. These marks might be needed for punching. Note that they are lost after trimming, since they lie outside the logical page. These marks are disabled by default.
- info, noinfo** — Print the page information consisting of filename, date, time, page number and page index on every sheet (see figure 1). The page index starts with #1 and is incremented with every page info line, hence being more reliable than page numbers, which are not unique and may be negative or contain letters. It can also be seen as a crop marks counter. Pages without crop marks aren’t counted. This page information is enabled by default.
- font** — The page info line uses `\normalfont` by default. If you are typesetting the document in non-latin glyphs or a decorative, but less legible font, you may want to request a specific font for that info. Just assign a font switching command like `\textsf` to the `font` option parameter, leaving the initial backslash away: `[font=\textsf{ }]`. This command may take one argument (like `\textsf{ }`) or stand alone (like `\small`). You can, of course, define a more complex command first, and assign that one: `\newcommand*\infofont[1]{\textcolor{blue}{\textsf{\small#1}}}` `\crop[font=infofont]`
- color** — You can set the color of crop marks, axes and info text with this option, if the `color` package could be loaded. The option takes only color names, as in `[color=red]`. See the `color` package documentation for how to define custom colors.
- mount1, mount2** — If more than one logical page is to be mounted on a physical sheet, you normally don’t want marks to appear on the inner edges, where the pages touch each other. The `mount2` option prints only the outer marks. There’s also a `mount1` option that is selected by default. These commands take a number as an optional argument serving as page offset. Type `mount2` or `mount2=0` for odd pages right and `mount2=1` for odd pages left. Since further modes are likely to be document, driver, and printer dependent, it is up to you to implement them yourself. (See a `mount4` suggestion on page 25.)



Figure 1: That’s what you see on top of a 9 cm wide document page when `cam` mode is requested: the marks, jobname, date, time, page number and crop marks index.

horigin, vorigin — The top and left margin are by default 1 inch wide. This can be changed using the dimensions `\oddsidemargin`, `\evensidemargin` and `\topmargin`. It’s more convenient, though, to let the `geometry` package define all these and further parameters. The options `horigin` and `vorigin` only move the marks and don’t change the page contents. *Using these options is almost always a mistake, so use them only as a last resort!* Both options take a (mandatory) dimension. These dimensions describe the way from the reference point—the upper left corner of the text block—to the upper left corner of the page in a Cartesian coordinate system. As both `horigin` and `vorigin` are by default `-1in`, you would for example write `horigin=-.6in` to move the marks by 0.4 inch to the right.

graphics, nographics — Color printouts are often more expensive than black-and-white ones, while their text quality is sometimes reduced. Therefore it may be desirable to create two versions of a document, one with only text and one with only graphics. Now you can feed the concerned pages to a color printer to print the `notext` version, and then to a mono laser printer with the `nographics` version. The `graphics` option turns graphics on again. You may want to mark up all colored pictures so that you can decide in the preamble, whether they shall be printed or not.

```
%\newcommand*\colorgraphic{} % print them;
%\newcommand*\colorgraphic{\crop[nographics]} % don't!
...
{\colorgraphic
\includegraphics{...}
\caption{...}
}
```

2.3 Loading

Since all marks lie outside the logical page, the horizontal and vertical offset should be set properly. Otherwise the marks are likely to be cut off by the DVI driver or the printer. Provided that you have declared the size of your printing paper, you can use the `center` option to center every logical page on the respective sheet.

There's, however, no harm in centering an A4 page on A4 paper, in which case both offsets are set to 0pt (unless, of course, you have set `\mag ≠ 1000`).

```
\documentclass[a5paper]{article} \documentclass[a5paper]{article}
\usepackage[cam,a4,center]{crop} \usepackage[a4,center]{crop}
\begin{document} \begin{document}
... ...
\end{document} ... ...
\end{document}
```

`\crop` You get corner markings at every page shipped out after a `cam`, `cross`, or `frame` mode request until you turn them off by typing `\crop[off]`, or the actual grouping level ends. Typing `\crop` without argument is equivalent to typing `\crop[cam,noaxes]`. Axis marks appear only together with one of the modes as listed above. If you only want one cover page for trimming, make sure that a page is actually output in the scope of `\crop`, for example:

```
\newpage
{\crop[cross,axes]\mbox{} \newpage}
```

2.4 Color support

The `crop` package always tries to load the `color` package. You can change the color of the physical page as usual by using the `\pagecolor` command in the preamble. But after that, within the `document` environment, `\pagecolor` is redefined to only color the logical page. The color of crop marks, axes marks and page info can independently be set via the `color` option. The options `invert` and `notext` override any color settings.

2.5 Custom document page size

The `crop` package respects any page layout that you specify by means of L^AT_EX dimensions. The following example uses the `geometry` package, which I strongly recommend. Let's assume you want to print a CD booklet ($4\frac{23}{32} \times 4\frac{3}{4}$ inch) on ISO-A4 paper:

```
\documentclass{article}
\usepackage[dvips=false,pdftex=false,vtex=false]{geometry}

\geometry{
    paperwidth=4.71875in,
    paperheight=4.75in,
    margin=2em,
    bottom=1.5em,
    nohead
}

\usepackage[cam,a4,center,dvips]{crop}
```

```
\begin{document}
...
\end{document}
```

Note that the `crop` package should always be requested after setting up the ‘geometry’. See the `geometry` documentation for details. Always disable all of `geometry`’s driver options. While this isn’t necessary in every case, it doesn’t hurt and it makes your document more portable. You never know how the local `geometry.cfg` file on other workstations looks like!

2.6 Custom printing paper sheet size

If you want to use one of the `center`, `dvips`, `pdftex`, `pdflatex`, `lualatex`, `lualatex` or `vtx` options together with non-standard printing paper, you can set it via the `width` and `height` option, or simply add the respective paper definition to your `crop.cfg` file (see 2.8). Let’s for example define a new `weird` paper format, whereby the first dimension shall describe the paper width. Don’t forget to request `true` dimensions, otherwise you will get really weird results with scaled documents.

```
\DeclareOption{weird}{\CROP@size{12truecm}{34truecm}}
```

Now you can use your new printing paper format like the pre-defined ones.

```
\usepackage[frame,weird,center]{crop}
```

If you don’t need that format regularly or don’t want to depend on a `crop.cfg` file, then you might prefer to declare the dimensions in the document:

```
\usepackage[frame,width=12truecm,height=34truecm,center]{crop}
```

2.7 Defining your own marks

If you need a funny mode, you can easily define it with only a couple of macros.
`\cropdef` The `\cropdef` command defines the mode switch. It takes as arguments: the name of a macro providing the page info (optional; enclosed in brackets), four macro names to be assigned to the upper left, the upper right, the lower left, and the lower right corner, each representing a `picture` with zero width and height, or `\relax`, and finally the mode name. The optional brackets may also be empty, if no page info is wanted, or contain the info code instead of a macro name.

```
\newcommand*\funnymarkA{}%           % a little x
\begin{picture}(0,0)
\thinlines\unitlength1pt
\put(-5,-5){\line(1,1){10}}
\put(-5,5){\line(1,-1){10}}
\end{picture}
```

```

\newcommand*\funnymarkB{%
    \begin{picture}(0,0)
        \unitlength1pt
        \put(0,0){\circle*{5}}
    \end{picture}%
}

\newcommand*\funnyinfo{funny page info}
\cropdef[\funnyinfo]\relax\funnymarkA\relax\funnymarkB{funny}

```

Now you can select your new mode by typing `\crop[funny]`.

Each of the axis marks is a `picture` that you can easily replace by some custom definition. There's no setup command like `\cropdef`, though. The kernel provides two 'hooks' that can be used to add local extensions. These are macros that default to `\relax`. The first, `\CROP@user@a`, is executed at every page, no matter if marks are shown or not, while the second, `\CROP@user@b` is only executed at pages that contain crop marks. Local definitions and modifications are ideally put into a local configuration file:

2.8 The configuration file

If you want to change the predefined settings or add new features, then create a file named '`crop.cfg`' and put it in a directory, where `TeX` can find it. This configuration file will then be loaded at the end of the `crop.sty` file, so you can redefine any settings or commands therein, select package options and even introduce new ones. But if you intend to give your documents to others, don't forget to give them the required configuration files, too! That's how such a file could look like:

```

% define a new printing paper size
\DeclareOption{special}{\CROP@size{22truecm}{37truecm}{}}

% make the internal time string (used in the page
% information) accessible in the whole document
\let\Time\CROP@time

% let's use a different font for the predefined page
% information (we could also have written
% \newcommand*\CROP@font[1]{\textsf{\#1}})
\crop[font=textsf]
\endinput

```

3 How the package works

3.1 The kernel mechanism

`TeX` outputs a page via the `\shipout` command. The `crop` package redefines `\shipout` to insert the requested marks before it outputs the page contents. It is

carefully designed to coexist peacefully with other packages, which use the same method (like the `everyshi` package by MARTIN SCHRÖDER, from whom I have in fact borrowed some ideas).

In addition to the crop marks every page gets an info line containing the job name, the current date and time, the page number and an index number printed on top. This line can be turned off (`noinfo`) and on (`info`) anywhere in the document.

3.2 Dependencies

3.2.1 latex.ltx

The package works with all L^AT_EX 2_< standard classes (tested with L^AT_EX 2_< 1997/12/01 and sporadically with later versions), it does not work with plain T_EX.

The `crop` package uses (and relies on) the internal L^AT_EX tokens `\hb@xt@`, `\filename@parse`, `\@classoptionslist`, `\@ifundefined`, `\@height`, `\@depth`, `\filename@base`, `\@width`, `\z@`, `\cne`, `\z@skip`, `\p@`, `\c@page`, `\@namedef`, `\@nameuse`, `\strip@pt`, `\two@digits`, `\count@`, `\dimen@`, `\@for`, `\@empty`, `\gobble` and `\@undefined`, all of which are expected to keep their current meaning in future L^AT_EX 2_< releases. The `crop` package will, however, be supported at least for some years, so you needn't worry about it.

3.2.2 color.sty

`crop`'s color handling depends on the `color` package. The following internal macros are used directly: `\@declaredcolor`, `\current@color`, `\set@color`, `\set@page@color` (Tested with `color.sty`, version 1.0i as of 1999/02/16.)

3.2.3 graphics.sty

`crop`'s driver detection, as well as the options `rotate` `mirror`, and `nographics` depend on the `graphics` package. The following internal macros are used directly: `\Gin@PS@raw`, `\Gin@include@graphics`, `\Gin@driver` (Tested with `graphics.sty`, version 1.0l as of 1999/02/16.)

3.2.4 ifluatex.sty

`crop`'s driver detection depends on the `ifluatex` package.

4 The implementation

4.1 Preamble

`\stockwidth` Make sure that `\stockwidth` and `\stockheight` are `\dimen` registers that hold
`\stockheight` the physical paper size. They are initially set to the paper size, but will be changed
`\CROP@index` by the size options. These registers are also used/provided by the `memoir` class
`\CROP@font`

and the `hyperref` package. The `\CROP@font` macro is by default empty and can be changed through the `font` option.

```

1 <*package>
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{crop}[2017/11/19 1.10 crop marks (mf)]
4 \RequirePackage{ifluatex}
5 \expandafter\ifx\csname stockwidth\endcsname\relax
6     \newdimen\stockwidth
7     \stockwidth\paperwidth
8 \fi
9 \expandafter\ifx\csname stockheight\endcsname\relax
10    \newdimen\stockheight
11    \stockheight\paperheight
12 \fi
13 \newcount\CROP@index
14 \CROP@index\z@
15 \newcommand*\CROP@font{}

```

`\CROP@stockcolor` Try to load the `color` package. It is needed for the `invert` and the `notext` option and, of course, for the modified `\pagecolor` command. Changing the meaning of `\current@color` looks dangerous, but it is only done if the `color` package couldn't be loaded, anyway.

```

16 \let\CROP@stockcolor\empty
17 \let\CROP@pagecolor\empty
18 \IfFileExists{color.sty}{%
19     \RequirePackage{color}%
20     \let\CROP@needscolor\empty
21 }{%
22     \newcommand*\CROP@needscolor{%
23         \PackageError{crop}{%
24             The 'invert' and 'notext' options require the\MessageBreak
25             'color' package, which doesn't seem to be installed%
26         }{%
27             Install the 'color' package or don't use the 'invert'
28             \MessageBreak or 'notext' option.
29         }%
30         \let\CROP@needscolor\relax
31     }%
32     \let\current@color\relax
33 }

```

4.2 The device drivers

`\CROP@detdriver` The options `graphics` and `nographics` depend on the `graphics` package, which, if configured appropriately, also tells us which output device is preferred on the system. Show a warning, if the package couldn't be loaded, because we have to use a less portable PS ‘driver’ then.

```
34 \let\CROP@detdriver\empty
```

```

35 \IfFileExists{graphics.sty}%
36   \RequirePackage{graphics}%
37   \let\CROP@Ginclude@graphics\Ginclude@graphics
38   \ifx\Gin@driver\@empty\else
39     \filename@parse{\Gin@driver}%
40     \edef\CROP@detdriver{\filename@base}%
41   \fi
42   \let\CROP@ps\Gin@PS@raw
43 }{%
44   \PackageWarning{crop}{I couldn't find the 'graphics' package, so
45   I'll use\MessageBreak my internal PostScript interface}%
46 }%
47 \newcommand*\CROP@ps[1]{\special{ps: ##1}}%
48 }

```

\CROP@reqdriver Define options that suggest ...

```

49 \let\CROP@reqdriver\@empty
50 \DeclareOption{vtex}{\def\CROP@reqdriver{vtex}}
51 \DeclareOption{pdftex}{\def\CROP@reqdriver{pdftex}}
52 \DeclareOption{pdflatex}{\def\CROP@reqdriver{pdflatex}}
53 \DeclareOption{luatex}{\def\CROP@reqdriver{luatex}}
54 \DeclareOption{lualatex}{\def\CROP@reqdriver{lualatex}}
55 \DeclareOption{dvips}{\def\CROP@reqdriver{dvips}}

```

\CROP@driver ... or enforce a graphics driver. Note the exclamation points!

```

56 \let\CROP@driver\@empty
57 \DeclareOption{vtex!}{\def\CROP@driver{vtex}}
58 \DeclareOption{pdftex!}{\def\CROP@driver{pdftex}}
59 \DeclareOption{pdflatex!}{\def\CROP@driver{pdflatex}}
60 \DeclareOption{luatex!}{\def\CROP@driver{luatex}}
61 \DeclareOption{lualatex!}{\def\CROP@driver{lualatex}}
62 \DeclareOption{dvips!}{\def\CROP@driver{dvips}}
63 \DeclareOption{nodriver}{\def\CROP@driver{none}}
64 \DeclareOption{!}{\def\CROP@driver{none}}

```

\CROP@evaldriver If \CROP@driver wasn't already set, decide \AtBeginDocument which graphics driver to use. A detected driver takes precedence over a 'suggested' one. Show a warning if the user's choice is ignored.

```

65 \newcommand*\CROP@evaldriver{%
66   \ifx\CROP@driver\@empty
67     \PackageInfo{crop}{requested driver: '\CROP@reqdriver'}%
68     \ifluatex
69       \def\CROP@detdriver{luatex}%
70     \else
71       \ifx\pdfoutput\undefined\else
72         \ifx\pdfoutput\relax\else
73           \ifcase\pdfoutput\else
74             \def\CROP@detdriver{pdftex}%
75           \fi

```

```

76          \fi
77      \fi
78  \fi
79  \ifx\VTeXversion\@undefined\else
80      \ifx\VTeXversion\relax\else
81          \def\CROP@detdriver{vtex}%
82      \fi
83  \fi
84  \PackageInfo{crop}{detected driver: '\CROP@detdriver'}%
85  \ifx\CROP@reqdriver\@empty\else
86      \ifx\CROP@reqdriver\@empty\else
87          \ifx\CROP@reqdriver\CROP@detdriver\else
88              \PackageWarningNoLine{crop}{%
89                  You requested the '\CROP@reqdriver' driver
90                  but I think that\MessageBreak the
91                  '\CROP@detdriver' driver works better in the
92                  current\MessageBreak context. You can force
93                  me to respect your decision\MessageBreak
94                  by adding an exclamation point as in
95                  [\CROP@reqdriver!]%
96              }%
97          \fi
98      \fi
99  \fi
100 \ifx\CROP@detdriver\@empty
101     \let\CROP@driver\CROP@reqdriver
102 \else
103     \let\CROP@driver\CROP@detdriver
104 \fi
105 \fi
106 \let\CROP@evaldriver\relax
107 }
108 \AtBeginDocument{\CROP@evaldriver}

```

\CROP@init@dvips These macros prepare the `crop` package for one of the supported graphics drivers.
 \CROP@init@pdftex They don't do anything spectacular, they just select the proper `rotate` and `mirror`
 \CROP@init@luatex macro and hand the physical paper size over to the driver program.

```

109 \newcommand*\CROP@init@dvips{%
110     \PackageInfo{crop}{using 'dvips' graphics driver}%
111     \AtBeginDvi{%
112         \special{papersize=\the\stockwidth,\the\stockheight}%
113     }%
114 }
115 \newcommand*\CROP@init@pdftex{%
116     \PackageInfo{crop}{using 'pdftex' graphics driver}%
117     \let\CROP@reflect\CROP@genreflect
118     \let\CROP@rotate\CROP@genrotate
119     \newcommand*\CROP@shiphook{%
120         \pdfpagewidth\stockwidth

```

```

121      \pdfpageheight\stockheight
122  }%
123 }
124 \newcommand*\CROP@init@luatex{%
125   \PackageInfo{crop}{using 'luatex' graphics driver}%
126   \pagewidth\stockwidth
127   \pageheight\stockheight
128   \let\CROP@reflect\CROP@genreflect
129   \let\CROP@rotate\CROP@genrotate
130 }
131 \newcommand*\CROP@init@vtx{%
132   \PackageInfo{crop}{using 'vtx' graphics driver}%
133   \mediawidth\stockwidth
134   \mediaheight\stockheight
135   \let\CROP@reflect\CROP@genreflect
136   \let\CROP@rotate\CROP@genrotate
137 }
138 \newcommand*\CROP@init@none{%
139   \PackageInfo{crop}{not using any graphics driver}%
140 }

```

4.3 Size options

\CROP@size These options set different standard printing paper sizes, which are needed for centering and as a hint for the dvips, pdftex, luatex or vtx program. Since the physical paper dimensions must not undergo a possible scaling, **true** dimensions are used. The **landscape** option exchanges the **\hoffset** and **\voffset** values.

```

141 \newcommand*\CROP@size[2]{\stockwidth#1 \stockheight#2 }
142 \DeclareOption{landscape}{%
143   \def\CROP@size#1#2{\stockheight#1 \stockwidth#2 }%
144 }
145 \DeclareOption{a0}{\CROP@size{841truemm}{1189truemm}}
146 \DeclareOption{a1}{\CROP@size{594truemm}{841truemm}}
147 \DeclareOption{a2}{\CROP@size{420truemm}{594truemm}}
148 \DeclareOption{a3}{\CROP@size{297truemm}{420truemm}}
149 \DeclareOption{a4}{\CROP@size{210truemm}{297truemm}}
150 \DeclareOption{a5}{\CROP@size{148truemm}{210truemm}}
151 \DeclareOption{a6}{\CROP@size{105truemm}{148truemm}}
152 \DeclareOption{b0}{\CROP@size{1000truemm}{1414truemm}}
153 \DeclareOption{b1}{\CROP@size{707truemm}{1000truemm}}
154 \DeclareOption{b2}{\CROP@size{500truemm}{707truemm}}
155 \DeclareOption{b3}{\CROP@size{353truemm}{500truemm}}
156 \DeclareOption{b4}{\CROP@size{250truemm}{353truemm}}
157 \DeclareOption{b5}{\CROP@size{176truemm}{250truemm}}
158 \DeclareOption{b6}{\CROP@size{125truemm}{176truemm}}
159 \DeclareOption{letter}{\CROP@size{8.5truein}{11truein}}
160 \DeclareOption{legal}{\CROP@size{8.5truein}{14truein}}
161 \DeclareOption{executive}{\CROP@size{7.25truein}{10.5truein}}
162 \newcommand{\CROP@opt@width}{\stockwidth\CROP@0}

```

```

163 \newcommand{\CROP@opt@height}{\stockheight\CROP@@}

\center The center option sets \voffset and \hoffset so that the document pages are
164 \DeclareOption{center}{\AtBeginDocument{\CROP@center}}
165 \newcommand*\CROP@center{%
166   \voffset\stockheight
167   \advance\voffset-\paperheight
168   \voffset.5\voffset
169   \hoffset\stockwidth
170   \advance\hoffset-\paperwidth
171   \hoffset.5\hoffset
172 }

```

4.4 Runtime options handling

Pass every unknown option to the macro \CROP@execopt.

```

173 \DeclareOption*{\CROP@execopt\CurrentOption}

\crop The \crop macro allows options to be used both in the preamble and throughout
the document. Every argument of the optional argument list is passed to the
macro \CROP@execopt. The options cam and noaxes are selected by default.
174 \newcommand*\crop[1][cam,noaxes]{%
175   \@for\CROP@:=#1\do{\CROP@execopt\CROP@@}%
176 }

\CROP@execopt Every execution of this macro with an argument n leads to the execution of a macro
\CROP@opt@n or a warning if no such exists. Optional arguments (separated by an
equal sign) are cut off and stored in \CROP@@. The macro tolerates even arguments
for options that are not prepared to handle arguments (e.g. cross=garbage), or
more than one argument (e.g. mount2=1=garbage). This makes the design simpler
and doesn't hurt.
177 \newcommand*\CROP@execopt[1]{%
178   \def\CROP@##1=##2=##3@nil{%
179     \expandafter\CROP@#1==\@nil%
180     \ifundefined{\CROP@opt@\CROP@}{%
181       \PackageError{crop}{%
182         Requested option '#1' not provided%
183       }{%
184         Note that the '*center' options are obsolete. You have to
185         request\MessageBreak e.g. [a4,center] instead of
186         [a4center].%
187       }%
188     }{%
189       \cnameuse{\CROP@opt@\CROP@}%
190     }%
191   }

```

\cropdef The \cropdef macro defines a mode switch (see section 2.7). It supports only corner marks and the page info, but not the axis marks, mainly for hysterical raisins.

```

192 \newcommand*\cropdef[6]{[\CROP@info]{%
193   @namedef{CROP@opt@#6}{%
194     \def\CROP@info{#1}%
195     \let\CROP@ulc#2
196     \let\CROP@urc#3
197     \let\CROP@llc#4
198     \let\CROP@lrc#5
199     \let\CROP@@marks\CROP@marks
200   }%
201 }

```

4.5 Axes and page info

\CROP@laxis The standard definitions for the axes option.

```

\CROP@raxis 202 \newcommand*\CROP@laxis{%
\CROP@upaxis 203   \begin{picture}(0,0)
\CROP@loaxis 204     \unitlength\p@\thinlines
205     \put(-2,0){\line(-1,0){11}}
206   \end{picture}%
207 }
208 \newcommand*\CROP@raxis{%
209   \begin{picture}(0,0)
210     \unitlength\p@\thinlines
211     \put(2,0){\line(1,0){11}}
212   \end{picture}%
213 }
214 \newcommand*\CROP@upaxis{%
215   \begin{picture}(0,0)
216     \unitlength\p@\thinlines
217     \put(0,2){\line(0,1){11}}
218   \end{picture}%
219 }
220 \newcommand*\CROP@loaxis{%
221   \begin{picture}(0,0)
222     \unitlength\p@\thinlines
223     \put(0,-2){\line(0,-1){11}}
224   \end{picture}%
225 }

```

\CROP@time This macro prints the jobname, the current date and time, the page number and an index number at the top of the logical page.

```

\CROP@opt@font 226 \newcommand*\CROP@time{}%
227 \bgroup
228   \count@\time
229   \divide\time60

```

```

230      \count\@ne\time
231      \multiply\time60
232      \advance\count@-\time
233      \xdef\CROP@time{\the\count\@ne:\two@digits{\count@}}
234 \egroup
235 \newcommand*\CROP@@info{%%
236   \global\advance\CROP@index\@ne
237   \def\x{\discretionary{}{}{\hbox{\kern.5em---\kern.5em}}}{%
238     \advance\paperwidth-20\p@
239     \dimen@4pt
240     \ifx\CROP@pagecolor\empty
241     \else
242       \advance\dimen@\CROP@overlap
243     \fi
244     \hb@xt@\z@{%
245       \hss
246       \vbox to\z@{%
247         \centering
248         \hsize\paperwidth
249         \vss
250         \normalfont
251         \normalsize
252         \expandafter\csname\CROP@font\endcsname{%
253           '\jobname'\x
254           \the\year/\the\month/\the\day\x
255           \CROP@time\x
256           page\kern.5em\thepage\x
257           \#\the\CROP@index
258           \strut
259         }%
260         \vskip\dimen@
261       }%
262       \hss
263     }%
264   }}
265 \newcommand*\CROP@opt@font{\let\CROP@font\CROP@@}

```

4.6 The marks

The following four macros provide different marks for the `cam` mode. They do not touch the logical page and can, thus, be printed on every single sheet.

`\CROP@@ulc` The `cam` mode corner mark for the upper left corner.

```

266 \newcommand*\CROP@@ulc{%
267   \begin{picture}(0,0)
268     \unitlength\p@\thinlines
269     \put(-30,0){\circle{10}}
270     \put(-30,-5){\line(0,1){10}}
271     \put(-35,0){\line(1,0){30}}

```

```

272      \put(0,30){\circle{10}}
273      \put(-5,30){\line(1,0){10}}
274      \put(0,35){\line(0,-1){30}}
275  \end{picture}%
276 }

```

\CROP@0urc The `cam` mode corner mark for the upper right corner.

```

277 \newcommand*\CROP@0urc{%
278   \begin{picture}(0,0)
279     \unitlength\p@\thinlines
280     \put(30,0){\circle{10}}
281     \put(30,-5){\line(0,1){10}}
282     \put(35,0){\line(-1,0){30}}
283     \put(0,30){\circle{10}}
284     \put(-5,30){\line(1,0){10}}
285     \put(0,35){\line(0,-1){30}}
286   \end{picture}%
287 }

```

\CROP@0llc The `cam` mode corner mark for the lower left corner.

```

288 \newcommand*\CROP@0llc{%
289   \begin{picture}(0,0)
290     \unitlength\p@\thinlines
291     \put(-30,0){\circle{10}}
292     \put(-30,-5){\line(0,1){10}}
293     \put(-35,0){\line(1,0){30}}
294     \put(0,-30){\circle{10}}
295     \put(-5,-30){\line(1,0){10}}
296     \put(0,-35){\line(0,1){30}}
297   \end{picture}%
298 }

```

\CROP@0lrc The `cam` mode corner mark for the lower right corner.

```

299 \newcommand*\CROP@0lrc{%
300   \begin{picture}(0,0)
301     \unitlength\p@\thinlines
302     \put(30,0){\circle{10}}
303     \put(30,-5){\line(0,1){10}}
304     \put(35,0){\line(-1,0){30}}
305     \put(0,-30){\circle{10}}
306     \put(-5,-30){\line(1,0){10}}
307     \put(0,-35){\line(0,1){30}}
308   \end{picture}%
309 }

```

\CROP@opt@cam Define the `cam` mode switch with four different marks.

```
310 \cropdef{\CROP@0ulc}{\CROP@0urc}{\CROP@0llc}{\CROP@0lrc}{cam}
```

\CROP@@cross This macro provides a 4 cm wide cross.

```
311 \newcommand*\CROP@@cross{%
312   \begin{picture}(0,0)
313     \unitlength1cm\thinlines
314     \put(-2,0){\line(1,0){4}}
315     \put(0,-2){\line(0,1){4}}
316   \end{picture}%
317 }
```

\CROP@opt@cross Define the **cross** mode switch with four times the same mark.

```
318 \cropdef\CROP@@cross\CROP@@cross\CROP@@cross{cross}
```

\CROP@@frame The **frame** mode draws a simple frame around the logical page. The frame mark is designed to be used in the upper left corner. Since graphics commands expect numbers without dimensions, **\paperwidth** and **-height** are transformed to numbers (representing printer's points). This is done by stripping off the unit **pt**.

```
319 \newcommand*\CROP@@frame{%
320   \begin{picture}(0,0)
321     \unitlength\p@\thinlines
322     \put(0,0){\line(1,0){\strip@pt\paperwidth}}
323     \put(0,0){\line(0,-1){\strip@pt\paperheight}}
324     \put(\strip@pt\paperwidth,0){\line(0,-1){\strip@pt\paperheight}}
325     \put(0,-\strip@pt\paperheight){\line(1,0){\strip@pt\paperwidth}}
326   \end{picture}%
327 }
```

\CROP@opt@frame Define the **frame** mode switch with only one mark. The other corners may **\relax**.

```
328 \cropdef\CROP@@frame\relax\relax\relax{frame}
```

4.7 The kernel

\CROP@shipout These macros redefine the T_EX primitive **\shipout** to insert the contents of the macro **\CROP@shiplist** on top of the box which contains the page contents ready for output, after which the original **\shipout** command is executed.

```
329 \let\CROP@shipout\shipout
330 \renewcommand*\shipout{%
331   \afterassignment\CROP@ship
332   \setbox\@cclv=%
333 }
334 \newcommand*\CROP@ship{%
335   \ifvoid\@cclv
336     \expandafter\aftergroup
337   \fi
338   \CROP@ship
339 }
340 \newcommand*\CROP@shiplist{%
341   \lineskip\z@
```

```

342      \lineskiplimit{z@}
343      \baselineskip{z@}
344      \CROP@kernel
345      \box@cclv
346 }
347 \newcommand*\CROP@@shipf{%
348     \csname CROP@shiphook\endcsname
349     \CROP@shipout\vbox{\CROP@shiplist}%
350 }

\CROP@shipadd This macro adds a page manipulation command to the shiplist, which gets every
ready page as argument.
351 \newcommand*\CROP@shipadd[1]{%
352     \bgroup
353         \toks@\expandafter{\expandafter#\expandafter{\CROP@shiplist}}%
354         \xdef\CROP@shiplist{\the\toks@}%
355     \egroup
356 }

\CROP@kernel \CROP@kernel essentially contains a \vbox with zero width and height. The
\CROP@marks \CROP@hook command—which normally equals \relax—allows to insert com-
\CROP@@marks mands that modify the behavior of the selected mode (see the options mount1
\CROP@setmarkcolor and mount2). \CROP@user@a and \CROP@user@b are user definable hooks.
\CROP@user@a 357 \newcommand*\CROP@kernel{%
\CROP@user@b 358     \vbox to{z@}{%
\CROP@opt@horigin 359         \vskip\CROP@vorigin
\CROP@opt@vorigin 360         \hb@xt@{z@}{%
361             \hskip\CROP@horigin
362             \vbox to{paperheight}{%
363                 \let\protect\relax
364                 \hsize\paperwidth
365                 \CROP@hook
366                 \CROP@user@a
367                 \CROP@drawstockcolor
368                 \CROP@drawpagecolor
369                 \CROP@@marks
370             }%
371             \hss
372         }%
373         \vss
374     }%
375 }
376 \newcommand*\CROP@marks{%
377     \CROP@setmarkcolor
378     \CROP@user@b
379     \CROP@ulc\null\hfill\CROP@@info\CROP@upedge\hfill\null\CROP@rc
380     \vfill
381     \CROP@ledge\hfill\CROP@redge
382     \vfill

```

```

383      \CROP@llc\null\hfill\CROP@loedge\hfill\null\CROP@lrc
384 }
385 \let\CROP@@marks\CROP@marks
386 \newcommand*\CROP@setmarkcolor{%
387     \let\current@color\CROP@markcolor
388     \set@color
389 }
390 \let\CROP@user@a\relax
391 \let\CROP@user@b\relax
392 \newcommand*\CROP@opt@horigin{\let\CROP@horigin\CROP@@}
393 \newcommand*\CROP@opt@vorigin{\let\CROP@vorigin\CROP@@}

\CROP@opt@off These macros start and stop the output of crop marks.
\CROP@opt@odd 394 \newcommand*\CROP@opt@off{%
\CROP@opt@even 395     \let\CROP@@marks\vfil
396 }
397 \newcommand*\CROP@opt@odd{%
398     \def\CROP@@marks{\ifodd\c@page\CROP@marks\else\vfil\fi}%
399 }
400 \newcommand*\CROP@opt@even{%
401     \def\CROP@@marks{\ifodd\c@page\vfil\else\CROP@marks\fi}%
402 }

\CROP@@info Enable and disable the output of axis marks and page info.
\CROP@opt@info 403 \newcommand*\CROP@@info{}
\CROP@opt@noinfo 404 \newcommand*\CROP@opt@info{\def\CROP@@info{\CROP@info}}
\CROP@opt@axes 405 \newcommand*\CROP@opt@noinfo{\let\CROP@@info\relax}
\CROP@opt@noaxes 406 \newcommand*\CROP@opt@axes{%
407     \let\CROP@ledge\CROP@laxis
408     \let\CROP@redge\CROP@raxis
409     \let\CROP@upedge\CROP@upaxis
410     \let\CROP@loedge\CROP@loaxis
411 }
412 \newcommand*\CROP@opt@noaxes{%
413     \let\CROP@ledge\relax
414     \let\CROP@redge\relax
415     \let\CROP@upedge\relax
416     \let\CROP@loedge\relax
417 }

```

4.8 Mounting

\CROP@opt@mount1 Since `\newcommand` doesn't allow macro names to contain non-letters, we need a construction with `\csname`, `\endcsname`, and `\expandafter`. `\@namedef` would have worked, too, but it would not have made a check for redefinitions.

```

418 \expandafter\newcommand\expandafter*\csname CROP@opt@mount1\endcsname{%
419     \let\CROP@hook\relax
420 }

```

```

421 \newcount\CROP@offset
422 \expandafter\newcommand\expandafter*\csname CROP@opt@mount2\endcsname{%
423   \CROP@offset=\ifx\CROP@@@\empty\z@\else\CROP@@\fi
424   \def\CROP@hook{%
425     \count@\c@page
426     \advance\count@\CROP@offset
427     \ifodd\count@
428       \let\CROP@ulc\relax
429       \let\CROP@llc\relax
430       \let\CROP@ledge\relax
431     \else
432       \let\CROP@urc\relax
433       \let\CROP@lrc\relax
434       \let\CROP@redge\relax
435     \fi
436   }%
437 }

```

4.9 Page manipulation

- \CROP@reflect The mirror and rotate options add a macro to the *shiplist*, which then gets every output page and embeds it in a POSTSCRIPT environment (*dvips*) or lets the *graphics* package reflect or rotate it (*pdftex* or *lualatex*). We could also use the generic operations \CROP@genreflect and \CROP@genrotate for the *dvips* mode. They would produce correct PS documents, the intermediate DVI document, however, would be unreadable.

```

438 \DeclareOption{mirror}{%
439   \AtBeginDocument{\CROP@shipadd\CROP@reflect}
440 }
441 \newcommand*\CROP@reflect[1]{%
442   \vbox to\z@{%
443     \vskip\CROP@vorigin
444     \hb@xt@\z@{%
445       \hskip\CROP@horigin
446       \CROP@ps{gsave currentpoint}%
447       \kern\paperwidth
448       \CROP@ps{currentpoint}%
449       \hss
450     }%
451     \vss
452   }%
453   \CROP@ps{translate -1 1 scale neg exch neg exch translate}%
454   \vbox{\#1}%
455   \CROP@ps{grestore}%
456 }
457 \newcommand*\CROP@genreflect[1]{%
458   \leavevmode
459   \dimen0\CROP@horigin
460   \kern2\dimen0

```

```

461      \reflectbox{%
462          \hb@xt@{\paperwidth}{%
463              \vbox to\paperheight{%
464                  #1%
465                  \vss
466              }%
467              \hss
468          }%
469      }%
470 }
471 \DeclareOption{rotate}{%
472     \AtBeginDocument{\CROP@shipadd\CROP@rotate}
473 }
474 \newcommand*\CROP@rotate[1]{%
475     \hb@xt@{z@{}}{%
476         \hskip\CROP@horigin
477         \vbox to{z@{}}{%
478             \vskip\CROP@vorigin
479             \CROP@ps{gsave currentpoint}%
480             \kern\paperheight
481             \hb@xt@{z@{}}{%
482                 \kern\paperwidth
483                 \CROP@ps{currentpoint}%
484                 \hss
485             }%
486             \vss
487         }%
488         \hss
489     }%
490     \CROP@ps{translate 180 rotate neg exch neg exch translate}%
491     \vbox{#1}%
492     \CROP@ps{grestore}%
493 }
494 \newcommand*\CROP@genrotate[1]{%
495     \dimen0\CROP@vorigin
496     \kern2\dimen0
497     \leavevmode
498     \dimen0\CROP@horigin
499     \kern2\dimen0
500     \rotatebox{180}{%
501         \hb@xt@{\paperwidth}{%
502             \vbox to\paperheight{%
503                 #1%
504                 \vss
505             }%
506             \hss
507         }%
508     }%
509 }

```

4.10 Color handling

```

\CR@P@stockcolor These macros care for the color of crop marks and of the logical and the physical
\CR@P@pagecolor page. The overlap value is the amount that the logical page is drawn over the
\set@page@color page boundaries on each side. This is necessary to get good results on imprecise
\CR@P@needscolor cutting machines.

\CR@P@defmarkcolor 510 \newcommand*\CR@P@defmarkcolor[1]{{%
\CR@P@opt@color 511     \def\set@color{\global\let\CR@P@markcolor\current@color}%
\CR@P@drawstockcolor 512     \Odeclaredcolor{\#1}%
\CR@P@drawpagecolor 513 }%
\CR@P@overlap 514 \ifx\CR@P@needscolor\empty
\CR@P@opt@overlap 515     \renewcommand*\set@page@color{%
516         \global\let\CR@P@stockcolor\current@color
517     }%
518     \AtBeginDocument{%
519         \def\set@page@color{%
520             \global\let\CR@P@pagecolor\current@color
521         }%
522     }%
523     \CR@P@defmarkcolor{black}%
524     \let\CR@P@needscolor\relax
525 \fi
526 \newcommand*\CR@P@opt@color{%
527     \CR@P@needscolor
528     \expandafter\CR@P@defmarkcolor\expandafter{\CR@P@O}%
529 }
530 \newcommand*\CR@P@drawstockcolor{%
531     \ifx\CR@P@stockcolor\empty
532     \else
533         \rlap{%
534             \smash{%
535                 \raise\voffset\hbox{%
536                     \let\current@color\CR@P@stockcolor
537                     \set@color
538                     \hskip-\voffset
539                     \vrule width\stockwidth height\z@ depth\stockheight
540                 }%
541             }%
542         }%
543     \fi
544 }
545 \newcommand*\CR@P@drawpagecolor{%
546     \ifx\CR@P@pagecolor\empty
547     \else
548         \rlap{%
549             \smash{%
550                 \dimen@\CR@P@overlap
551                 \advance\paperwidth2\dimen@
552                 \advance\paperheight2\dimen@

```

```

553           \raise\dimen@\hbox{%
554             \let\current@color\CR0P@pagecolor
555             \set@color
556             \hskip-\dimen@
557             \vrule width\paperwidth height\z@ depth\paperheight
558           }%
559         }%
560       }%
561     \fi
562   }%
563 \def\CR0P@overlap{3truemm}
564 \newcommand*\CR0P@opt@overlap{\let\CR0P@overlap\CR0P@@}

```

- \CR0P@invert** The invert option simply switches to black background and white text, after which it disables all color switching commands. The notext option does the same with white text on white background. The `\@gobble` on the last line keeps notext from switching to white background and breaking a prior invert.

```

565 \newcommand*\CR0P@invert[1]{%
566   \CR0P@needscolor
567   \AtBeginDvi{%
568     \pagecolor{#1}%
569     \global\let\set@page@color\relax
570     \global\let\CR0P@setpagecolor\relax
571   }%
572   \color{white}%
573   \DeclareRobustCommand*\color[2][]{\color{#1}%
574     \let\pagecolor\color
575     \let\textcolor\color
576     \let\CR0P@invert\@gobble
577   }%
578   \DeclareOption{invert}{%
579     \CR0P@invert{black}%
580     \let\CR0P@setmarkcolor\relax
581   }%
582   \DeclareOption{notext}{%
583     \CR0P@invert{white}%
584 }

```

4.11 The graphics commands

- \CR0P@opt@nographics** The nographics option redefines the `\Ginclude@graphics` command from the `graphics` package, so that it outputs its argument as a phantom. This makes the image invisible but takes up the same amount of white space. The `graphics` option re-enables `graphics`.

```

585 \newcommand*\CR0P@opt@nographics{%
586   \def\Ginclude@graphics##1{%
587     \phantom{%
588       \CR0P@Ginclude@graphics{##1}%
589     }%
590   }%
591 }

```

2	1
0	3

Figure 2: Possible `mount4` arrangement

```

589      }%
590      }%
591 }%
592 \newcommand*\CROP@opt@graphics{%
593   \let\Ginclude@graphics\CROP@Ginclude@graphics
594 }

```

4.12 Final settings

`\CROP@horigin` Switch off marks and axes, set one page per sheet, load the local configuration file, `\CROP@vorigin` and process the requested options. Finally: Exit.

Notice that we cannot simply use `\ExecuteOptions` to preselect options `off`, `noaxes`, `info`, and `mount1`, because it does not accept default options declared with `\DeclareOption*`. `\nameuse` doesn't complain if the command sequence is undefined. We let this only be executed `\AtBeginDocument`, because there are possibly commands from the `center` option in the queue that have to be processed first.

```

595 \newcommand*\CROP@horigin{-1truein}
596 \newcommand*\CROP@vorigin{-1truein}
597 \crop[cam,off,noaxes,info,mount1]
598 \InputIfFileExists{crop.cfg}{%
599   \PackageInfo{crop}{Local config file crop.cfg used}
600 }{}%
601 \ProcessOptions
602 \AtBeginDocument{\nameuse{\CROP@init@\CROP@driver}}
603 \endinput
604 
```

4.13 A `mount4` example

Since a `mount4` mode is likely to be subject to specific local needs, there's only a suggestion provided, which supports a page arrangement as shown in figure 2.

First of all `\CROP@offset` is set to the value of the (optional) argument or zero. Then `\CROP@hook` is defined first to set `\count0` to the page number increased by this offset: $p = \text{pagenumber} + \text{offset}$.

```

\expandafter\newcommand\expandafter*\csname CROP@opt@mount4\endcsname{%
  \CROP@offset=\ifx\CROP@@\empty\z@\else\CROP@@\fi
  \def\CROP@hook{%

```

```
\count@c@page
\advance\count@\CROP@offset
```

Now bits 0 and 1 are checked via \ifodd to get p modulo 4, after which the respective marks are deleted. The comments in the example use for simplicity C-notation in which ‘%’ is the modulo or remainder operator, ‘==’ the equal, and ‘||’ the logical (inclusive) OR operator.

```
\ifodd\count@                                %% if (p % 4 == 1 || p % 4 == 3)
  \let\CROP@ulc\relax
  \let\CROP@llc\relax
  \let\CROP@ledge\relax
  \divide\count@2
  \ifodd\count@                                %% if (p % 4 == 3)
    \let\CROP@urc\relax
    \let\CROP@info\relax
    \let\CROP@upedge\relax
  \else                                         %% if (p % 4 == 1)
    \let\CROP@lrc\relax
    \let\CROP@loedge\relax
  \fi
\else                                         %% if (p % 4 == 0 || p % 4 == 2)
  \let\CROP@urc\relax
  \let\CROP@lrc\relax
  \let\CROP@redge\relax
  \divide\count@2
  \ifodd\count@                                %% if (p % 4 == 2)
    \let\CROP@llc\relax
    \let\CROP@loedge\relax
  \else                                         %% if (p % 4 == 0)
    \let\CROP@ulc\relax
    \let\CROP@info\relax
    \let\CROP@upedge\relax
  \fi
\fi
} %
```